Vectra XL 750 & XL 950 Liquid Ring Vacuum Pump & Compressor







Vectra XL vacuum pumps and compressors are created to meet exacting performance and design standards.

They combine the highest standard of reliability with a new level of ingenuity. Gardner Denver Nash employs advanced design technologies to achieve optimum performance and unprecedented production efficiencies.

Production efficiencies ultimately passed on to our customers in the form of unique value and unequaled performance.

Features	Benefits		
Compact design	Less floor space required		
External mechanical seals	Flexibility & ease of maintenance		
Universal stuffing box	Accepts variety of mech. seals		
Global product design	Wide range of direct drive speeds		
Extended pressure ratings	Ability to handle tough applications where back pressure is required		
Conical design	Better ability to handle water/particulate slugs		
One moving part	Long term reliability		
Variable port design	High efficiency		
Lobe purges	Reduce erosion wear		
NASH patented Gas Scavenging	Increased performance at high vacuum levels		
Available in Ductile Iron and 316L S/S	Material flexibility		
Optimum design using finite element analysis	Improved efficiency, performance and value		
100% performance tested	Trouble-free start-up and operation		
'			





Dimensions

Pump	А	В	С	D	Е	Inlet	Outlet
XL 750	81.5 2070	49 1244	47.3 1200	20.5 520	5.1 130	10 in. FLG. 250mm FLG.	8 in. FLG. 200mm FLG.
XL 950	89.5 2273	55.4 1407	53.5 1360	23.2 590		12 in. FLG. 300mm FLG.	10 in. FLG. 250mm FLG.

All dimensions are approximate

Basic specifications

Vacuum range	0-28.5 in Hg Vac. to 50 mbar abs.
Mechanical seals*	Single or double cartridge
Differential pressure capability	30 psi 2 bar
Hydrotest pressure	150 psig / 11 bar abs. standard (225 psig / 16 bar abs. optional)
Construction material	Ductile iron, stainless steel

^{*} Packing is supplied as standard. Mechanical seals are optional.